Coastal AgroBusiness, Inc.



Safety Data Sheet

Kleen-Tac "85"

SDS Number: 11040 SDS Prepared: 02/15/1986

SDS Version: 4.0

Version Date: 07/13/2013

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Kleen-Tac "85"

CHEMICAL NAME: n-Octanol; n-Decanol

CHEMICAL FAMILY: Linear Fatty Alcohols

SYNONYMS: C₈ Fatty Alcohol, C₁₀ Fatty Alcohol (Octyl Alcohol, Decyl Alcohol)

COMMON NAME: Octanol, Decanol

EPA REGISTRATION NUMBER: 5549-74

Manufactured by: **Emergency Telephone Numbers**

Coastal AgroBusiness Inc. Chemtec (24 hours) PO Box 856 1800-424-9300

Greenville, NC 27835 Coastal AgroBusiness, Inc. (Weekdays – Eastern Standard Time)

Phone: 1-800-635-1388 1-800-635-1388

2. HAZARDS IDENTIFICATION SUMMARY

KEEP OUT OF REACH OF CHILDREN - CAUTION- Do not inhale mists. Avoid contact with eyes, skin and clothing. May cause irritation. Use with adequate ventilation. Wash thoroughly after handling.

This product is a clear, colorless to golden liquid with a sweet, pungent odor. Primary routes of entry are inhalation, eve contact and skin contact

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:	Percentage by	CAS No.	PEL/TLV
	Weight:		
n-Octanol (Fatty Alcohol c ₈₎	35.5%	111-87-5	NE/NE
n-Deconal (Fatty Alcohol C ₁₀)	49.5%	112-30-1	NE/NE
Emulsifier Blend	15.0%	9005-65-6	NE/NE
*Formulated from a fatty alcohol mixture that typically contains: C ₆ -1.0%, C ₈ -41.0%, C ₁₀ -57.0%, C ₁₂ -0.8% Linear Fatty Alcohols.			

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least fifteen minutes, holding eyelids apart to

ensure flushing of the entire eye surface. Do not let victim rub eyes. Seek medical attention.

SKIN: Remove contaminated clothing and wash with large amounts of soap and water. If irritation

develops, contact a physician.

Call a physician immediately. If instructed to have the victim drink fluids, do not give sodium INGESTION:

bicarbonate, fruit juices or vinegar. Only induce vomiting at the instruction of a physician.

Remove person from area of exposure. Give artificial respiration if necessary. If breathing is **INHALATION:**

difficult, give oxygen if qualified operator is available. Seek immediate medical attention.

SAFETY DATA SHEET Kleen-Tac "85"

5. FIRE FIGHTING MEASURES

FLASH POINT (°F/Test Method): 245.6°F (118.7°C); FLAMMABLE LIMITS (LFL & UFL): Not established

EXTINGUISHING MEDIA: Water spray, CO₂, dry chemical, foam None known

HAZARDOUS COMBUSTION

PRODUCTS:

SPECIAL FIRE FIGHTING Cool exposed equipment with water spray. Self-contained positive

pressure breathing apparatus should be worn when there is a PROCEDURES: possibility of exposure to smoke, fumes or hazardous decomposition products. If spill or leak has not ignited, use water spray to disperse the vapors. Water spray may be used to flush spills away from fire

and to dilute spills to nonflammable mixtures.

UNUSUAL FIRE AND EXPLOSION

Fatty alcohols are an NFPA Class IIIB combustible liquid.

HAZARDS:

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Small spills: Eliminate all sources of ignition. Evacuate the area. Contain the spill with dikes or absorbents to prevent migration and entry into sewers, streams or drinking water supplies. Take up with dry chemical absorbents and place into suitable container for disposal.

Large Spills: Eliminate all sources of ignition. Evacuate the area. Contain spill to prevent migration and entry into sewers, streams or drinking water supplies. Spills may be taken up with pump or vacuum and finished with dry chemical absorbents. May require excavation of contaminated soil.

CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

7. HANDLING AND STORAGE

Avoid contact with eyes. Use only in a well-ventilated area. Wash thoroughly after handling. **HANDLING:**

Avoid prolonged or repeated breathing of vapors. Avoid prolonged or repeated contact with

Store away from sources of ignition and in a cool, dry place. Tanks: Carbon steel with STORAGE:

effective moisture control, baked phenolic, epoxy or polyester, or metallic zinc in an inorganic binder. Special precautions: Inert gas blanket and breathing system needed to maintain color

stability. Use dry inert gas having at least -40°F dew point.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

THRESHOLD LIMIT VALUE: No ACGIH TVL PERMISSIBLE EXPOSURE LIMIT: No OSHA PEL

SIGNS AND SYMPTOMS OF

EXPOSURE:

In high concentrations, vapor may cause irritation of the nose and throat,

Should not be a hazard at ambient dizziness, and headache. temperatures. Repeated or prolonged contact can cause reddening and scaling of the skin. May cause corneal inflammation. A chronic

overexposure may cause depression of the central nervous system.

Dermatitis

MEDICAL CONDITIONS

GENERALLY AGGRAVATED BY

EXPOSURE:

PRIMARY ROUTES OF ENTRY: May be harmful if vapor/mist are inhaled at high concentration. No specific

data available for ingestion. Moderate eye irritant. Mild skin irritant.

Use adequate exhaust ventilation to prevent inhalation of product vapors. **ENGINEERING CONTROLS:** NIOSH-approved organic air-purifying respirator, self-contained breathing RESPIRATORY PROTECTION:

apparatus, or air-supplied respirators dependent on concentration.

When contact with liquid is possible, use a face shield or splash goggles, **EYE PROTECTION:**

otherwise use safety glasses.

SKIN PROTECTION: Use full protective clothing, boots and gloves when in contact with liquid. SAFETY DATA SHEET Kleen-Tac "85"

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND COLOR: Clear, colorless to golden liquid, sweet pungent odor.

SPECIFIC GRAVITY: (Water=1): 0.86

VAPOR PRESSURE: 1 mm Hg @ 70 °F (Fatty Alcohol Mixture)

VAPOR DENSITY (Air = 1): 4.5 (Fatty Alcohol Mixture)

% VOLATILITY (V/V): 85%

BOILING POINT: 401-459°F (205-237°C) (Fatty Alcohol Mixture)

MELTING POINT:5.9°F (-14.5°C)SOLUBILITY:Emulsifies

pH: 6.04

VISCOSITY @ 22°C: 18.6 mm (cStokes)

Note: These physical data are typical values based on material tested but may vary from sample to

sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as

specification items.

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: High Temperatures

INCOMPATIBILITY: Strong oxidizers, inorganic acids and halogens

HAZARDOUS DECOMPOSITION Decomposition of organic materials may produce oxides of carbon

PRODUCTS:

HAZARDOUS POLYMERIZATION: Will not occur

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL LD₅₀: 28.3 g/kg

EYE IRRITATION: 29.3 Irritation Index

INHALATION LC₅₀: No effects at one-hour exposure to 31 mg/L.

CARCINOGENETIC POTENTIAL: This product is not mutagenic, teratogenic, or carcinogenic.

ACUTE DERMAL LD₅₀: 1.75 g/kg

SKIN IRRITATION/SENSITIZATION: 4.8 Irritation Index

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Do not reuse container. Place in trash or offer for recycling. Incinerate contaminated solids in accordance with local, state, and federal regulations.

Waste Disposal Methods: Do not contaminate water, food or feed by storage or disposal. Waste resulting from spills of this material are not subject to CERCLA/RCRA regulations. Therefore, it may be disposed of as an industrial waste in a manner acceptable to good waste management practice and in compliance with applicable Local, State and Federal regulations.

14. TRANSPORTATION INFORMATION

D.O.T. Shipping Description: NOT REGULATED BY DOT BY HIGHWAY.

Consult appropriate ICAO/IATA and IMDG regulations for shipment requirements in the Air and Maritime shipping modes.

SAFETY DATA SHEET Kleen-Tac "85"

15. REGULATORY INFORMATION

NFPA & HMIS Hazard Ratings:

NFPA
1 Health
1 Health

1 Flammability 1 Flammability 1 Reactivity 1 Reactivity H PPE

SARA Hazard Notification/Reporting

SARA Title III Hazard Category: Immediate: \underline{Y} Fire: \underline{N} Delayed: \underline{N} Reactive: \underline{N}

Sudden Release of Pressure: N

Reportable Quantity (RQ) under U.S. None

CERCLA:

SARA, Title III, Section 313: Contains no chemical subject to SARA 313

SARA, Title III, Section 302:

RCRA Waste Code:

CA Proposition 65:

EHS None
TPQ 10,000 lbs
Not listed
Not listed

16. OTHER INFORMATION

SDS STATUS: Updated

REASON FOR CHANGE:To meet new regulatory requirements

PREPARED BY: Tandy O. Dunn, Director of Health, Safety & Environmental Affairs

Disclaimer and Limitation of Liability: This data sheet was developed from information on the constituent materials identified herein and does not relate to the use of such materials in combination with any other material or process. No warranty is expressed or implied with respect to the completeness or ongoing accuracy of the information contained in this data sheet, and Coastal AgroBusiness, Inc. disclaims all liability for reliance on such information. This data sheet is not a guarantee of safety. Users are responsible for ensuring that they have all current information necessary to safely use the product described by this data sheet for their specific purpose.

